

Cylinder BL0T2*00H*

Disposable screw-down 5- & 8-kg/h cylinder for 3-phase immersed electrode humidifiers

Technical features

Single use (disposable) 3-phase steam cylinders suitable for:

- **KUE02** humidification kits and
- 3-phase **humiSteam UE005Y/X*** and **UE008Y/X*** humidifiers
- Body: PPh plastic, class HB according to UL94
- Steam outlet: Ø 30mm
- Manifold connection: Ø 22mm
- Water volume: max 5,5 lt.
- Galvanised steel electrodes
- Electric connection: threaded M6; 10mm nuts and isolating caps supplied
- AFS sensor contacts
- Full body scale filter
- Max steam production: 8kg/h
- Max steam pressure: 0,002 Mpa
- Water conductivity range: see table

Approved water conductivity ranges:

Cylinder Model	kg/h	VAC	µS/cm
BL0T2A00H1	5-8	200, 208, 230 3-phase	75-350
BL0T2B00H0	5-8	200, 208, 230 3-phase	350-1250
BL0T2B00H0	5-8	400 3-phase	75-350
BL0T2C00H0	5-8	400 3-phase	350-750
BL0T2D00H0	5-8	400 3-phase	750-1250
BL0T2C00H0	5-8	460, 575 3-phase	75-350
BL0T2D00H0	5-8	460, 575 3-phase	350-1250

More details in Carel instruction sheet +050003970

